

# Pro-Guide<sup>®</sup> CHARGERS



12/24/36/48V  
LiFePO4 MODELS  
LITHIUM WAKE FEATURE  
BUILT-IN COOLING FAN  
IP66

## PRO-GUIDE<sup>®</sup> ON/OFF BOARD CHARGERS

SKU	PGC-1230	PGC-2420	PGC-3615	PGC-4815
INPUT VOLTAGE	AC 110-120V, 40-70HZ			
OUTPUT VOLTAGE	DC 12V X1	DC 24V X1	DC 36V X1	DC 48V X1
MAX CHARGING VOLTAGE	14.6	29.2	43.8	58.4
MAX CHARGING CURRENT	30A	20A	15A	15A
CHEMISTRY	LiFePO4			
CHARGING PROTECTION	OVERCHARGE, OVERCURRENT, OVERTEMP, SHORT CIRCUIT, AND REVERSE POLARITY PROTECTION			
WEIGHT (LBS)		3.75 LBS		6.6 LBS
WEIGHT (KG)		1.7 KGS		3 KGS
DIMENSIONS (INCH)		L 7.19 W 4.13 H 2.5		L 11.13 W 4.88 H 2.81
DIMENSIONS (MM)		L 182 W 105 H 65		L 282 W 124 H 72