

STARTING
PGLU1X
 12.8V / PbEq 390CCA / 3AH / 36WH



PRO-GUIDE®

UNIT SPECIFICATIONS

Nominal Voltage	12.8V
Nominal Capacity	3Ah
Stored Energy	36Wh
PbEq CCA	390CCA
Protection Level	IP65
Terminal	M6
Discharge Cut off Voltage	8V
Charge Cut off Voltage	15.3V
Standard Charge Current	1.5A
Max Continuous Charge Current	15A
Self Discharge	<3% Per Month
Cycle Life	>1000 times @ 100% DOD

TEMPERATURE SPECIFICATIONS

Operating Temperature	
Charging Temperature	-4F - 113F (-20C - 45C)
Discharging Temperature	-4F - 140F (-20C - 60C)
Storage Temperature	
3 Months	-4F - 104F (-20C to 40C)
1 Year	-4F - 104F (-20C to 40C)

MEASUREMENTS

Length	6.85in
Width	4.84in
Height	6.42in
Weight	2.76lbs

The Pro-Guide Lithium U1X is a high-performance starting battery designed for Lawn & Garden equipment and other small engine applications, delivering 390 Cold Cranking Amps for reliable starts in any season. It features convenient Quad Terminals, a built-in State of Charge gauge, and Pro-Boost technology for enhanced starting power. Backed by a 3-year warranty, the U1X is built to start strong and last long.

