



# PRO-GUIDE<sup>®</sup>

## QUICK START INSTALLATION STEPS

### ATTENTION:

Before installing, make sure that all appliances are turned off.

1. Open the golf cart compartment, you will see your original lead-acid or AGM batteries.
2. Take a photo of the wiring setup or draw a template to insure you reconnect all cables to the correct terminal.
3. Disconnect all the wires safely and pull out your old batteries.
4. Fasten the bracket we offer in the compartment as the base if needed.
5. Install the charger into the compartment.
6. Replace your old receptacle with the new one we offer (for safety, this step is necessary).
7. Install the gauge and ON/OFF switch on dashboard of your cart.
8. Install the wiring harness which will be used to connect battery communication port, ON/OFF button, and gauge.
9. Before placing pack into cart, ensure the power button is off and there is no voltage to the terminals
10. Install the appropriate mounting bracket into your cart if needed
11. Put the battery pack into compartment and fasten the pack to the bracket base
12. Connect wiring harness with battery ON/OFF button and gauge
13. Connect battery positive and negative terminal to positive and negative of your cart
14. Connect battery positive and negative terminal to positive and negative of the charger
  - A. Mount the voltage converter, connect to the battery and accessories if needed
  - B. For EZ-GO RXV, attach the blue wire from the old receptacle to the positive terminal of the battery
15. Now you can turn on the ON/OFF button to check the cart powers on and is functional.
16. After installation, charge the battery fully.
17. Register the battery at <https://proguidebatteries.com/product-registration/>

Installation by an authorized technician is encouraged, but installation can be done when instructions are fully followed. Call 1-800-827-3232 for troubleshooting support.